



RT-65 Compact Track Loader



RT-65 Brief Specifications

| | |
|---------------------|----------------------|
| Operating weight: | 7,630 lbs 3,461 kg |
| Tipping load: | 5,500 lbs 2,495 kg |
| Ground pressure: | 4.3 psi 29.7 kPa |
| Gross engine power: | 67 hp 50 kW |

SPECIFICATIONS

RT-65

OPERATING SPECIFICATIONS

| | |
|--|---------------------|
| Loader arms | Radial |
| Operating weight | 7630 lbs 3461 kg |
| Shipping weight | 6938 lbs 3147 kg |
| Ground pressure @ operating weight | 4.3 psi 29.7 kPa |
| Rated operating capacity, 35% of tipping load | 1925 lbs 873 kg |
| Operating capacity, 50% of tipping load | 2250 lbs 1247 kg |
| Tipping load | 5500 lbs 2495 kg |
| Travel speed, maximum | 10.6 mph 17.1 kph |
| Attachments | Variable |

ENGINE

| | |
|-------------------------------|---|
| Type | Diesel, 3-cylinder, turbocharged, after-cooled |
| Model | Deutz TCD 2.2 T4 |
| Displacement | 134 in ³ 2.2 L |
| Gross power rating @ 2800 rpm | 67 hp 50 kW |
| Torque, peak | 184.4 ft-lb 250 Nm |
| Cooling system | Engine-driven fan and coolant/ anti-freeze-filled radiator |
| Intake air cleaner | Dual stage |
| Emission controls | Meets all U.S. EPA Tier 4 final standards |

UNDERCARRIAGE

| | |
|---------------------------|--|
| Track type | General purpose track constructed of rubber compound with embedded co-polymer cords and all-purpose treads. Single row of track drive lugs molded in. Turf track with smooth tread available as an option. |
| Track width | 15 in 381 mm |
| Length of track on ground | 59 in 1499 mm |
| Ground contact area | 1770 in ² 1.14 m ² |
| Drive system | Two hydrostatic direct drive sprockets controlled by a single joystick |
| Track drive sprocket | Elevated with low friction, replaceable sprocket rollers |
| Undercarriage suspension | Two independent torsion axles per undercarriage |
| Roller wheels | 12 high-density polyurethane and rubber wheels per track Wheels include sealed bearings |
| Roller wheel diameter: | |
| Front wheels | 14 in 365 mm |
| Other wheels | 10 in 254 mm |

AUX. HYDRAULIC SYSTEM

| | |
|-----------------------|--|
| Pump capacity | 103.7 lpm (HF Model) / 84 lpm (SF Model) |
| System pressure, max. | 3300 psi 22753 kPa |
| Controls | Pilot Hydraulic Joystick Control (LH = speed/direction, RH = loader), Work Port Relief |
| Couplers | Push-to-connect quick couplers mounted on loader arms (SF Models) / Hydraulic Quick Hitch (HF Model) Pressure relief valve mounted to coupler block |
| Cooling system | High-efficiency hydraulic oil cooler beside (not stacked) engine radiator |

ELECTRICAL SYSTEM

| | |
|-----------------|---|
| Nominal charge | 12 V |
| Battery | 800 CCA |
| Charging system | 120 amp alternator |
| Outlets | 1-12 V port inside operator station |
| Wiring | Pre-wired for all factory-available accessories |


OPERATOR STATION

| | |
|-------------------------|---|
| Seat: | Adjustable contour vinyl with built-in operator presence switch, lap bar and 2 in 51 mm wide seat belt |
| Loader control: | Right-hand pilot hydraulic joystick controls loader lift/lower and tilt, plus intermittent control of auxiliary hydraulic |
| Drive control: | Left-hand pilot hydraulic joystick controls machine speed and direction |
| Engine speed | Foot pedal & hand-operated electronic throttle lever |
| Multifunctional display | Fuel, Tachometer, Trip Meter, Battery Engine Temperature, Hour Meter, Hydraulic Temperature, Water Temperature, Danfoss Computer + AM/FM Radio (enclosed cab models only) Multiple Languages |
| ROPS | Meets SAE J1040 MAY94, ISO 3471 |
| FOPS | Meets SAE J1043 SEPT87, ISO 3449 |
| Illumination | 2 - Fixed forward-facing halogen lights 2 - Adjustable rear-facing halogen lights 1 - Interior light |
| Convenience | 12 V power port |
| Horn | |
| Backup alarm | |

* Machine tested with foundry bucket

DIMENSIONS

RT-65



- A. Full Length: 141.5 in. | 3594 mm
- B. Arm-Up Height: 116.5 in. | 2959 mm
- C. Machine Height: 81.4 in. | 2067 mm
- D. Width: 66 in. | 1676 mm
- E. Ground Clearance: 13 in. | 330 mm

SPECIFICATIONS

RT-65

SERVICE REFILL CAPACITIES

| | |
|------------------------------|--------------------|
| Fuel tank | 23.2 gal 87.8 L |
| Hydraulic tank | 3.3 gal 12.5 L |
| Engine coolant/antifreeze | 2.5 gal 9.5 L |
| Engine oil, including filter | 8.5 quarts 8.0 L |

OPTIONAL ATTACHMENTS

| | |
|-------------------------|-------------------|
| Auger drive and bits | Std Flow Mulcher |
| Backhoe | High Flow Mulcher |
| Broom, rotary | Grapple bucket |
| Bucket, general purpose | Pallet forks |
| Bucket, light material | Power box rake |
| Bucket, multi-purpose | Stump grinder |
| Brush cutter, rotary | Trencher |
| Dozer blade | Vibratory roller |
| Eliminator rake | |



Effective Date: AUGUST 2019

Product specifications and prices are subject to change without notice or obligation. The photographs and/or drawings in this document are for illustrative purposes only. Refer to the appropriate Operator's Manual for instructions on the proper use of this equipment. Failure to follow the appropriate Operator's Manual when using our equipment or to otherwise act irresponsibly may result in serious injury or death. The only warranty applicable to our equipment is the standard written warranty applicable to the particular product and sale and ASV makes no other warranty, express or implied. © 2016, ASV LLC. ASV, the ASV logo design and Positrack are trademarks of ASV, LLC.

ASV, LLC

840 Lily Lane
Grand Rapids, MN
55744-4089

Toll-free: (800) 205-9913
Fax: (218) 327-2297
www.asvllc.com

